

Technical data sheet for

SINGLE PAN ELECTRIC PASTA COOKER 450mm

PC8140E, PC8140E7



- High performance single pan pasta cooker
PC8140E 10.5kW 3 phase
PC8140E7 7.0kW 1 phase
- Heavy-duty 3 coil Incoloy 825 element
- Easy clean 316 grade stainless steel open pan
- 40L water capacity
- Intergrated water fill and starch skimming water faucet
- Six stainless steel pasta baskets supplied standard
- Incorporated basket drain stand
- Safety cut out thermostat for empty pan/water boil out
- Stainless steel exterior
- Easy service
- Fully modular

Series Options

- PC - Standard splashback models
- PCL - Low back models
- PCB - Bold vitreous enamel colour front finish on standard splashback models
- PCLB - Bold vitreous enamel colour front finish on low back models

Overall Construction

- Pan 1.5mm 316 stainless steel with 10 year limited warranty
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.5mm 304 stainless steel
- Side panels 1.2mm 304 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- 25mm (1") skimming overflow and pan drains drain valve
- 150mm legs in 63mm dia. heavy-duty 1.2mm 304 stainless steel with adjustable feet
- 6 stainless steel baskets with moulded handle grips supplied standard (no lid on pasta cooker)
- 304 stainless steel wire basket support grid in pan

Controls

- Large easy to use knob - heat resistant reinforced
- 3 power settings (boil-simmer-standby)
- Mechanical thermostat
- Thermostat range 30°C - 110°C
- Fail safe over-temperature safety cut-out
- Element tilt switch for heating cut-out
- Indicator lights for power & heating
- Fine adjustment water faucet for pan filling and water refreshing/starch skimming

Cleaning and Servicing

- Open stainless steel pan for easy clean
- Hinged basket drain stand
- Removable basket support grid
- 25mm (1") drain valve for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit

Technical data sheet for SINGLE PAN ELECTRIC PASTA COOKER 450mm



Australia
www.moffat.com.au
New Zealand
www.moffat.co.nz

Australia
Moffat Pty Limited

Victoria/Tasmania
740 Springvale Road
Mulgrave, Victoria 3170
Telephone 03-9518 3888
Facsimile 03-9518 3833
vsales@moffat.com.au

New South Wales
Telephone 02-8833 4111
nswsales@moffat.com.au

South Australia
Telephone 03-9518 3888
vsales@moffat.com.au

Queensland
Telephone 07-3630 8600
qldsales@moffat.com.au

Western Australia
Telephone 08-9202 6820
bgarcia@moffat.com.au

New Zealand
Moffat Limited

Christchurch
Telephone 03-389 1007
sales@moffat.co.nz

Auckland
Telephone 09-574 3150
sales@moffat.co.nz



Designed and manufactured by



ISO9001

All Waldorf products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

Specifications

Pan Size

Water capacity 40L

Width 365mm

Length 405mm

Basket immersion depth 165mm

Baskets

6 stainless steel perforated baskets with moulded plastic handles 125mm x 165mm x 180mm deep

Stainless steel wire basket support grid

Elements

1 x 10.5kW Incoloy 825 heating element (PC8140E)

1 x 7.0kW Incoloy 825 heating element (PC8140E7)

Electrical Requirements

PC8140E

10.5kW, 400-415V, 50/60Hz, 3P+N+E

L1 14.6A

L2 14.6A

L3 14.6A

PC8140E7

7.0kW, 220-240V, 50/60Hz, 1P+N+E

L1 29.2A

Electrical Connection

56mm from RH side, 541mm from rear and

489mm from floor

Water Connection

Cold water connection 50mm from left hand side, 556mm from rear and 140mm from floor

R $\frac{1}{2}$ (BSP) male

Drain Connection

Drain must be connected to system suitable for boiling water discharge

1" BSP Male connection 118mm from left hand side, 470mm from rear, and 165mm from floor

Dimensions

Width 450mm

Depth 805mm

Height 915mm

Incl. splashback 1130mm

Packing data

0.53m³

Width 865mm

Depth 490mm

Height 1255mm

Options at extra cost

Extra baskets - 165mm square x 180mm deep

Optional rectangular baskets 320mm x 165mm x 180mm deep

Side splash guards

Joining caps

Castors

Plinth mounting

PC8140G

